

D 2.135 2.125 С - 0.625 - $\phi_{0.575}^{0.585}$ $\ \ \phi_{0.300}^{0.305}$ 100° Ø0.385 $\phi_{0.438}^{0.448}$ R0.01 R0.02 2 PL 4 PL Ø0.189 THRU **SECTION A-A D5832-3 STOP** (DERIVED FROM AERO DESIGN P/N 95931-10) NOTES:
1) MATERIAL: 6061-T6/T651/T6510/T6511/T62 ALUMINUM ROUND BAR
PER QQ-A-225/8 OR AMS-QQ-A-225/8
(OR AMS 4117/4128/4115/4116) OR QQ-A-200/8 OR AMS-QQ-A-200/8
(OR AMS 4160) OR ASTM B211 OR ASTM B221
REF DART SPEC M6061T6R
2) FINISH: ANODIZE PER MIL-PRF-8625 TYPE II CLASS 2 BLACK
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX DESIGN RF **DART AEROSPACE LTD** RELEASED **DRAWN** JC **APPROVED** HAWKESBURY, ONTARIO, CANADA DRAWING NO. CHECKED ZF REV. B 2021 MAY 26 g 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1 D5832 MFG. APPR. FΚ SHEET 2 OF 2 APPROVED TITLE CP SCALE 7) WEIGHT: 0.03 lbs **LEVER** DE APPR. CP M NTS COPYRIGHT @ 2020 BY DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPPED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT DATE 20.12.16 WRITTEN PERMISSION FROM DART AEROSPACE LTD 3